



Revised 25.8.10

POR-15 AUTOMOTIVE FUEL TANK REPAIR KIT

Application Information

As we cannot control the quality of preparation and application done by owners or their agents we do not approve this product for use in aircraft or built in boat petrol tanks.

AUTOMOTIVE FUEL TANK REPAIR KIT
PLEASE READ THIS INFORMATION CAREFULLY BEFORE ATTEMPTING TO REPAIR YOUR FUEL TANK.

Kit Contains:
4 Litres Marine Clean
1 Litre Metal Ready
1 Litre Tank Sealer
1 x telescopic mirror

SUGGESTED SUPPLEMENTAL SUPPLIES

- Latex Gloves
- Eye Protection
- Bucket and access to hot water and a garden hose
- Soft rags for wiping any chemical spills on the exterior of the tank
- Duct tape for sealing up openings in the tank (petcock hole, etc).
- Work bench and/or soft padding to lay the tank on.
- Sandpaper.

THESE DIRECTIONS ARE FOR STEEL TANKS ONLY

It is important to understand each product in your repair kit and how it works because proper chemical interaction is essential for achieving the best possible bond of the sealer to the inside of the tank.

THE NATURE OF FUEL

All organic fossil fuels (gasoline, diesel fuel, fuel oil, etc) gradually deteriorate if left unused in a tank. If a tank "sits" for months or years, gum and varnish deposits form on the walls of the tank and are very difficult to remove. Often, it is hard to see this contamination because the tank looks okay even though the deposits are present. It is always best to assume there is foreign matter or contamination in a tank you wish to restore, even though that tank may appear to be perfectly clean.

MARINE CLEAN:

This is the first product you will use in the restoration of your fuel tank. Marine Clean is a very powerful cleaner that will break down gum and varnish deposits in your fuel tank, but it will take time and often repeated application. A hot solution of Marine Clean is more effective than a cold solution. Marine Clean is caustic and alkaline and therefore your tank must be neutralised and acidified before fuel tank sealer can be used most effectively.

METAL READY:

Metal Ready is an excellent prep for any coating or paint product, and it is essential that it be used before Fuel Tank Sealer is applied to your tank. Metal Ready is also a rust remover and will dissolve all the rust and scale that has formed in your tank. In instances of heavily built-up rust formed over many years of neglect, the application and use of Metal Ready will enable your POR-15 Fuel Tank Sealer to chemically bond with whatever rust may remain in the tank and form a permanent non-porous barrier against further rusting. The primary job of Metal Ready is to change the ph of your tank from alkaline to acid, and etch it. Coatings and paints stick much better to acid-prepped metals. Be sure to rinse your tank thoroughly with water afterward, to neutralising the surface. You may notice a white / salt and pepper look which is correct.

TANK SEALER:

The Tank Sealer in your kit is impervious to all conventional automotive and diesel fuels, including ethanol blends. The most important thing to remember is that your tank must be totally, completely, bone-dry before the sealer can be poured into it.

DIRECTIONS:

The preparation products, though non-toxic, should be handled with latex gloves and eye protection.

1. PREPARATION:

Empty the tank of all fuel and rinse out with clean water; remove fuel petcock, float, filters, fittings, etc. Seal up those openings in the tank with duct tape or cork to keep the solutions in the tank when you clean, prep and seal the tank.

- #### 2.
- Outside painted surface of your tank should be protected from preparation and sealing products with soft rags or other suitable protection.

3. MARINE CLEAN:

This product cleans varnish and rust out of the tank. It leaves the metal surface alkaline, the tank must be treated with Metal Ready to create an acidic surface for the sealant to stick to. **GLOVES AND EYE PROTECTION SHOULD BE WORN AT ALL TIMES.**

Mix 2 litres of **Marine Clean** and 1 litre of **Very Warm** (not scalding hot) water. Extremely hot water could melt the adhesive on the duct tape.

NOTE: The higher temperature of the water helps to activate the chemical process of the cleaner.

Pour the mixture into the tank, shake vigorously, and "roll" the tank around to ensure the cleaner gets to all inside surfaces for a minimum of 20 minutes. Now empty the solution from the tank and rinse it out with water. Repeat the procedure with the remaining 2 litres of Marine Clean and rinse well with water.

4. METAL READY:

This product makes the metal surface acidic and removes rust, which is necessary for the sealer to effectively bond to the surface.

NOTE: Tank should be empty of rinsing water but does not have to be dry before using Metal Ready.

Pour the entire bottle of Metal Ready into the tank.

Roll the tank around in all directions, for a minimum of 30 minutes to ensure it coats and remains wet on all surfaces or place the tank in different positions, every half an hour until the entire inside of the tank has been treated with Metal Ready. Metal Ready should not be in the tank longer than approx. 2 hours. Rinse the tank thoroughly with **WARM**—not scalding hot water several times and drain it thoroughly (low spots in the tank collect water so be sure to roll tank around to get as much water out as possible).

POR-15 AUTOMOTIVE FUEL TANK REPAIR KIT - continued

In order to get the tank completely dry, you must blow warm air into it because no tank will dry out on the inside by itself. The only way to do this job is to use forced air. This can be accomplished by using a hair dryer or hot air gun.

TANKS MUST BE COMPLETELY DRY INSIDE BEFORE SEALING. THE SEALER WILL NOT STICK TO A DAMP OR WET TANK. USE THE TELESCOPIC MIRROR TO CHECK.

No shortcuts, please. If any moisture is present in the tank when you pour in the sealer. **IT WILL NOT WORK PROPERLY** and all your hard work will be wasted

NOTE: Once the metal is treated, it can flash rust. Though the coating is designed to bond with any flash rust, ideally you will want to perform the forced air drying promptly after draining the tank and coat the tank with sealant soon after drying it.

4. PATCHING:

If you have any big exterior to interior leaks we recommend performing this step before the sealant step.

There are several methods to fix holes, but you must fix them **BEFORE** you put the **POR-15** Sealer into the tank.

First, remove all paint around area to be patched and rough it up with sandpaper. Soak area with Metal Ready and keep wet for a minimum of 30 minutes, then rinse with water and dry. Next, paint area with a liberal amount of Fuel Tank Sealer and place a small piece of repair cloth (provided) over the wet painted area.

Now, paint sealer over repair cloth from the centre outward so that the painted cloth is stretched evenly over repaired area. Apply a second coat 3-5 hrs later. Let patched area dry for 96 hours.

The tank cleaning process may reveal new leaks in the tank after removing rust and rust deposits from weakened and thin tank walls. These areas are likely to be in the low points and seams, especially if there are low tank areas below the level of the petcock. These areas may have collected water from tank condensation and water in your fuel and over time may corrode the tank metal. Carefully check these areas for leaks when you have fluid in there (it will only be a very small trickle if there is a pinhole leak.)

5. US Tank Sealer:

Open the POR-15 US Tank Sealer and stir until a uniform colour is achieved. Pour entire contents of can into the tank. Roll the tank **SLOWLY** 360 deg to ensure it coats the inside uniformly. You have about 20 min for this. In tanks with seams, and with low areas below the opening through which you are draining the sealant (typically the petcock hole) the sealant will puddle. Take great care to ensure you've drained out the excess. Any pooled material can cause you trouble later (pooled sealer can bubble and leave pin holes).

Slight "pressurisation" will ensure that the sealer is forced into the seams.

When you feel you have full coverage of the tank pour out the excess.

Use the mirror to check the coverage.

WARNING:

RETURN USED SEALER FROM THE TANK TO THE CAN. DO NOT RE-SEAL WITH THE LID. Any moisture present could cause the sealer to rapidly release carbon dioxide. **LEAVE THE LID OFF** so the tank sealer cures letting the carbon dioxide disperse and the tank sealer to harden.

IMPORTANT:

This is a very strong and durable coating. Take care to immediately clean surfaces on which you may have spilled the sealer. Any sealer remaining on painted surfaces will become permanent. Any excess sealer must be cleaned from screw hole threads for the petcock before it dries. A clean soft rag can be twisted into the screw holes to clean the material out. A cotton bud is also effective for this job.

Leave the tank 3-5 days upside down to cure before pouring in fuel.

CAUTION: Used sealer can not be re-used again. Pour it into the can or another container. **DO NOT SEAL** and let it sit until the next day when the sealer is hardened. It can then be disposed of according to local regulations for paint cans.

Please remember these instructions are general guide lines only and cannot and do not cover every application and environment. If you remain unsure as how to proceed, please call toll-free for technical advice on 1800 643 229

Have you tried our

Fuel Preservative?

It will keep your Petrol and Diesel

fresh for up to 2 years

Imported and distributed by:
PERMANENT PAINTED COATINGS PTY LTD
1/4 Prosperity Parade,
Warriewood, NSW 2102.

For your nearest retail outlet
PHONE FREE 1-800 643 229;
Phone 02 9999 0122
Fax: 02 9999 0394

Website: www.por15.com.au
Email: sales@ppcco.com.au



The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations or suggestions are made without guarantee.

Since the conditions of use of the Products sold by Permanent Painted Coatings Pty Ltd (are beyond the control of PPC ("the company"), the Company to the full extent allowed by law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein.

The Company warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Company make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Company with respect to any breach of the aforesaid warranty shall be limited, at the option of the Company, to payment of the cost of replacing the Products or of acquiring equivalent products and in no case shall the Company be liable for consequential loss or damage.

In no case will the Company be liable to defend or pay any award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Company hereby expressly disclaim any written or unwritten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.

09.08.10